

Basic series 800A

Wall safe with double bit lock



Characteristics


Made with Laser system technology

- "High tech" laser cutting, monobloc front frame with cutting gap between frame and door of only 2/10 mm
- Monobloc front in 8 mm thick special steel
- Full compartment opening
- Oversized hinge with self-lubricating bushes, anchored to the front in a secluded position
- Fully robotized high-resistance welding
- Epoxy painting with double phosphating
- Special door stops specifically designed to effectively resist break-in attempts with a sledgehammer
- Anchoring fins obtained on the four sides of the bottom with anti-tear function

Locking system

- Lock with double-bitted key, two throws, 6 asymmetric levers with independent springs, with direct pulling of the bolts
- 18 mm Carbonitrided and Nickel-plated Steel Rotating Deadbolts (22 mm from size 1803)
- Extraction of the inhibited key with the lock open.
- 2 keys supplied.

Products code and information



Code	Measures mm		Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
	External	Internal					
	LPH	LPH					
800A	260*180*150	240*160*105	2	-	1	7,0	4,00
801A	310*210*150	290*190*105	2	1	1	9,0	5,80
801PA	310*210*195	290*190*140	2	1	1	10,0	7,70
802A	360*230*195	340*210*140	2	1	1	12,0	10,00
803A	400*250*195	380*230*140	2 + 2	1	1	14,0	12,30
804A	420*280*195	400*260*140	2 + 2	1	1	17,5	14,60
805A	490*320*195	470*300*140	2 + 2	1	1	21,5	19,80