STARK

Standing safes

Seriea Basic N3800A

Mobile safe with double bit lock



Characteristics

Made with Laser system technology

- "High tech" laser cutting, monobloc front frame with cutting gap between frame and door of only 2/10 mm
- 3 mm special steel structure and 8 mm thick front
- Full compartment opening
- Oversized hinge with self-lubricating bushes, anchored to the front in a defiled position
- Fully robotized high-resistance welding
- Epoxy painting with double phosphating
- Special door stops specifically designed to effectively resist break-in attempts with a sledgehammer
- Anchoring holes on the bottom and back
- Supplied with fixing plugs
- Removable shelves

Locking system

- Lock with double-bitted key, two throws, 6 asymmetric levers with independent springs, with direct pulling of the bolts
- 18 mm Carbonitrided and Nickel-plated Steel Rotating Deadbolts (22 mm from size N3xx5A and up)
- Extraction of the inhibited key with the lock open.
- 2 keys supplied.

Products code and information



Code	Measures mm						
	External LPH	Internal LPH	Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
N3803A	375*260*300	369*254*249	2 + 2	1	1	19,5	23,40
N3806A	470*300*350	464*294*299	2 + 2	1	1	28,0	40,80
N3807A	416*500*400	410*494*344	2 + 2	2	1	37,0	69,70