

Series KONIKA 1250CE

Certified wall safe



Characteristics


Wall-mounted safety cabinet with security level S2 according to EN 14450:2017 and ECB.S C10

- **Shatterproof, made with 45° 3D Laser System technology, whose cut between door and frame prevents it from breaking.**
- "High tech" laser cutting, monobloc front frame with cutting gap between frame and door of only 2/10 mm • Monobloc front in 10 mm thick special steel
- Full compartment opening
- Oversized hinge with self-lubricating bushes, anchored to the front in a defiled position
- Fully robotized high-resistance welding Epoxy painting with double phosphating
- Special door stops specifically designed to effectively resist break-in attempts with a sledgehammer
- Anchoring fins obtained on the four sides of the bottom with anti-tear function

Locking system

- **Class A High Security Electronic Lock Certified according to EN 1300:2018 and ECB.S C10**
- Electronic release lock with motorized deadbolt drive
- Microprocessor with proprietary technology
- Deadbolts in carbonitrided and nickel-plated steel, diameter 22 mm
- User code from 6 to 10 digits or letters
- Non-volatile memory for code retention in the absence of power
- 12-key membrane keyboard
- Audible and optical feedback with red and green LED of typing, error, low batteries
- Powered by 1 9 Volt Alkaline battery (NO rechargeable batteries)
- Keypad lock (20") after 3 incorrect code entries
- External emergency power supply via contacts on the keypad.

Products code and information



Code	Measures mm		Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
	External	Internal					
	LPH	LPH					
1251CE	310*210*150	290*190*97	2	1	1	11,0	5,80
1251PCE	310*210*195	290*190*142	2	1	1	11,5	7,70
1252CE	360*230*195	340*210*142	2	1	1	14,5	10,00
1252PCE	360*230*240	340*210*187	2	1	1	15,0	14,00
1253CE	400*250*195	380*230*142	2 + 2	1	1	17,5	13,90
1253PCE	400*250*240	380*230*187	2 + 2	1	1	18,0	17,00
1254CE	420*280*195	400*260*142	2 + 2	1	1	19,5	15,60
1254PCE	420*280*240	400*260*187	2 + 2	1	1	20,0	20,30
1255CE	490*320*195	470*300*142	3 + 2	1	1	25,5	21,15
1255PCE	490*320*240	470*300*187	3 + 2	1	1	28,5	27,50
1256CE	490*420*220	470*400*167	3 + 2	1	1	31,5	33,00
1256PCE	490*420*280	470*400*227	3 + 2	1	1	32,5	44,18
1257CE	442*615*220	422*595*167	3 + 2	2	1	44,0	44,00
1257PCE	442*615*280	422*595*227	3 + 2	2	1	45,5	59,00