

Series CASSAFORTISSIMA 250CCE

Certificate wall safe









Characteristics





Wall-mounted safety cabinet with security level S2 according to EN 14450:2017 and ECB.S C10


- Shatterproof and resistant to the cutting disc, made with 45° 3D Laser System technology, whose cut between the door and the frame prevents it from breaking through and is also resistant to break-ins from the cutting disc since the door is equipped with a plate made with latest generation synthetic minerals.
- High-tech laser cutting, monobloc front frame with cutting gap between frame and door of only 2/10 mm
- Monobloc front in 10 thick special steel + 10 mm anti-cut plate
- Opening to the entire compartment
- Oversize hinge with self-lubricating bushes, anchored to the front in a secluded position
- Fully robotized high-resistance welding
- Epoxy painting with double phosphating
- Special door stops specifically designed to effectively resist break-in attempts with a sledgehammer
- Anchoring fins obtained on the four sides of the bottom with anti-tear function

Locking system

Class A High Security Electronic Lock certified according to EN 1300:2018 and ECB.S C10

- Electronic release lock with motorized deadbolt drive
- Microprocessor with proprietary technology
- Deadbolts in carbonitrided and nickel-plated steel, diameter 22 mm
- User code from 6 to 10 digits or letters
- Non-volatile memory for code retention in the absence of power
- 12-key membrane keyboard
- Audible and optical feedback with red and green LED of typing, error, low batteries
- Powered by 1 9 Volt Alkaline battery (NO rechargeable batteries)
- Keypad lock (20") after 3 incorrect code entries
- External emergency power supply via contact on the keypad.

Products code and information



Code	Measures mm						
	External LPH	Internal LPH	Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
251PCCE	310*210*195	290*190*144	2	1	1	11,5	7,70
252CCE	360*230*195	340*210*144	2	1	1	14,5	10,00
252PCCE	360*230*240	340*210*189	2	1	1	15,0	14,00
253CCE	400*250*195	380*230*144	2	1	1	17,5	13,90
253PCCE	400*250*240	380*230*189	2	1	1	18,0	17,00
254CCE	420*280*195	400*260*144	2 + 2	1	1	19,5	15,60
254PCCE	420*280*240	400*260*189	2 + 2	1	1	20,0	20,30
255CCE	490*320*195	470*300*144	3 + 2	1	1	25,5	21,15
255PCCE	490*320*240	470*300*189	3 + 2	1	1	28,5	27,50
256CCE	490*420*220	470*400*169	3 + 2	1	1	31,5	33,00
253PCCE	490*420*280	470*400*229	3 + 2	1	1	32,5	44,18
257CCE	442*615*220	422*595*169	3 + 2	2	1	44,0	44,00
257PCCE	442*615*280	422*595*229	3 + 2	2	1	45,5	59,00