

Series TOP LINE 18 MM – 450N

Wall safe with certified self-powered KABA electronic lock



Characteristics

Wall safety cabinet tested according to EN1143-1


• **Shatter-proof, Drill-proof, Resistant to drilling with a drill and cutting with a blowtorch, made with 3D Laser System technology, whose cut between the door and the frame prevents it from breaking through and is also resistant to break-ins from a cutting disc, drill and flame Oxyhydric since the door is made with "Wafer" technology with materials with melting points at different temperatures.**

- "High tech" laser cutting, monobloc front frame with cutting gap between frame and door of only 2/10 mm
- Very thick hinge with self-lubricating bushes, anchored to the front in a secluded position which allows the entire compartment to be opened
- Fully robotized high-resistance welding
- Anthracite finish with baked paint
- Door and frame constructed in a **"Wafer" shape with steel/manganese/steel 10+2+6 mm** to increase resistance to cutting with an oxyhydrogen flame
- Steel/manganese anti-drill plate 6+2 mm to protect the lock
- Stop between door and step frame for total protection against breaking
- Anchoring fins obtained on the four sides of the bottom with an "anti-tear" function
- Removable shelves

Locking system

- **KABA Electronic Digital lock, High security certified VDS grade II, CNPP, SIS and UL**
- Self-powered electronic lock that allows complete independence from external or battery power.
- Keyboard with 10 numeric keys + 2 function keys
- Anti-manipulation lock after 5 incorrect attempts (the lock goes into self-protection for 3 minutes)
- Optional: Unlocking with Double Code, to open the door you need 2 joint codes, 2 operators (mutual control)
- External dimensions 40 mm thick.
- VDS grade II, CNPP, SIS and UL approved.

Products code and information



Code	Measures mm		Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
	External	Internal					
	LPH	LPH					
455N	502*195*332	482*140*312	2	-	1	37,0	21,70
455NP	502*240*332	482*180*312	2	1	1	39,0	27,10
456N	502*220*432	482*160*412	2	1	1	44,5	31,80
456NP	502*280*432	482*220*412	2	1	1	46,5	43,70
456NP	502*280*432	482*220*412	2	1	1	46,5	43,70
456NPP	502*380*432	482*320*412	2	1	1	49,0	63,60
457N	454*220*629	434*160*609	2 + 2	1	1	63,0	42,30
457NP	454*280*629	434*220*609	2 + 2	1	1	65,0	58,20
407NPP	454*380*629	434*320*609	2 + 2	1	1	68,0	84,60