

## Series CH

Heavy mobile security safes



## Characteristics


### Mobile safety cabinet with Grade 1 safety level according to EN 1143

- The armor uses materials with characteristics and performances capable of resisting attacks conducted with thermal and mechanical means according to the requirements of the European standard EN 1143
- To protect the closing systems, special anti-drill and anti-oxyhydrogen flame devices have been adopted
- The closure is carried out by n. 5 movable rectangular bolts operated by a handle and n. 3 fixed anti-tear bolts on the hinge side. The doors are mounted on adjustable hinges, with rotating pins on self-lubricating material and allow opening up to 180°
- The safes are designed for anchoring to the floor and wall via fixing holes.
- n. 2 anchor holes (1 on the back, 1 on the base)
- Removable shelves

### Locking system

- Deadbolt advancement handle with half stop Lock with EN1300B certified double-bitted key + 3-disc combination

Products code and information



Code	Measures mm		Bolts	Shelves	Sales Unit	Weight Kg	Volume Lt
	External	Internal					
	LPH	LPH					
CH20CB	510*360*400	385*175*275	2+2	1	1	120,0	18,60
CH30CB	510*520*600	385*335*475	3+2	2	1	190,0	62,00
C390	510*450*800	385*265*675	3+2	3	1	240,0	69,00
C391	510*520*1000	385*335*875	3+2	3	1	290,0	113,00
C392	610*520*1200	485*335*1075	3+2	3	1	390,0	175,00